

## Magix 10kW DC-Pulse Bias 1-30kHz

<b>Output Power:</b>	10kW
<b>Regulation type:</b>	U (V), I (A), P (W)
<b>Control command:</b>	Analog (0 - 10 V) RS-232 Profibus DP (optional) RS485 (optional)
<b>Digital Input/Output:</b>	4 inputs 4 outputs (software customized I/O)
<b>Analog/Output:</b>	Real output value, voltage, current or power (0 - 10 V)
<b>Output voltage:</b>	20 - 1000VDC « TAPLESS »
<b>Output current:</b>	0-30A
<b>Frequency:</b>	1-30kHz, 1kHz increments
<b>Pulse duty cycle:</b>	1% to 99%
<b>Arc control:</b>	reaction time < 1.5us, selectable Different modes of detection, selectable
<b>Accuracy:</b>	< 0.5 %
<b>Repeatability:</b>	< 0.2 %
<hr/>	
<b>Input Voltage:</b>	400V +/- 10%, 3 phase, 50/60Hz no neutral required
<b>Input Current:</b>	22A nominal per phase
<hr/>	
<b>Size:</b>	19" rack ( 4U ) 180mm(H) x 483mm(W) x 660mm(D) (incl. connectors)
<b>Weight:</b>	33kg
<b>Operating temperature:</b>	+5°C to + 40°C
<b>relative humidity:</b>	max 85% non-condensing
<b>air pressure:</b>	80 kPa to 106 kPa
<b>Cooling:</b>	air cool, front - air inlet, rear - air outlet

## Magix 10kW DC-Pulse IGBT Bias

